


4 Zatiči Dowel Pin

DIN 1 /K-70/K-80/ ISO 2339



Konični zatič.

Conical Dowel Pin.

Obdelava:

Po želji kaljeno, fino brušeno na toleranco h10.

Material:

Orodno jeklo

Trdota:

HRC 58-62

Primer naročila:

Konični zatič premera 6 mm in dolžine 60 mm, kaljen:

Konični zatič: K-70 $\varnothing 6 \times 60$

Finish:

Optionally hardened, fine ground to ISO tolerance h10.

Material:

Tool steel

Hardness:

HRC 58-62

Order example:

Conical dowel pin: 6 x 60 mm, hardened:

Conical Pin: K-70 $\varnothing 6 \times 60$



d	h10	0,6	0,8	1	1,5	2	2,5	3	4	5	6	8	10	12	14	16	20	25	30	40	50	
c	max.	0,1	0,12	0,15	0,23	0,3	0,4	0,45	0,6	0,75	0,9	1,2	1,5	1,8	2	2,5	3	4	4,5	6	7,5	
r	≈	0,6	0,8	1	1,5	2	2,5	3	4	5	6	8	10	12	16	16	20	25	32	40	50	
L	js 15																					
4		●																				
6		●	●																			
8		●	●	●																		
10		●	●	●	●																	
12			●	●	●	●	●															
14			●	●	●	●	●	●														
16				●	●	●	●	●	●													
18				●	●	●	●	●	●	●												
20					●	●	●	●	●	●	●											
(22)					●	●	●	●	●	●	●	●										
24					●	●	●	●	●	●	●	●	●									
(26)						●	●	●	●	●	●	●	●	●								
28						●	●	●	●	●	●	●	●	●	●							
(30)						●	●	●	●	●	●	●	●	●	●	●						
32						●	●	●	●	●	●	●	●	●	●	●	●					
36						●	●	●	●	●	●	●	●	●	●	●	●	●				
40							●	●	●	●	●	●	●	●	●	●	●	●	●			
45								●	●	●	●	●	●	●	●	●	●	●	●	●		
50									●	●	●	●	●	●	●	●	●	●	●	●	●	
55										●	●	●	●	●	●	●	●	●	●	●	●	●
60										●	●	●	●	●	●	●	●	●	●	●	●	●
70										●	●	●	●	●	●	●	●	●	●	●	●	●
80											●	●	●	●	●	●	●	●	●	●	●	●
90											●	●	●	●	●	●	●	●	●	●	●	●
100												●	●	●	●	●	●	●	●	●	●	●
110												●	●	●	●	●	●	●	●	●	●	●
120												●	●	●	●	●	●	●	●	●	●	●
130													●	●	●	●	●	●	●	●	●	●
140													●	●	●	●	●	●	●	●	●	●
150														●	●	●	●	●	●	●	●	●
165															●	●	●	●	●	●	●	●
180																●	●	●	●	●	●	●
200																	●	●	●	●	●	●
230																		●	●	●	●	●
260																				●	●	●